

elipson® | Prestige Facet **SUB12**

CAISSON DE BASSE 2 VOIES BASS-REFLEX

La gamme Prestige Facet Sub s'élargit avec le nouveau caisson de basses actif PF Sub 12.

Ce caisson de basse est équipé d'un haut-parleur de 30 cm avec une membrane en fibre de verre pour une réponse de fréquence optimale grâce son comportement pistonique. Il est conçu en mode bass-reflex « Down Firing » dans un boîtier rigide et inerte, amplifié par un module de 500 W en classe D.

Il possède également une base amovible qui permet de l'utiliser en mode clos en y insérant un cylindre de mousse dense dans l'évent.

En mode bass-reflex, il offre un impact du registre grave autour de la fréquence centrale de 40 Hz pour des systèmes Home Cinéma.

En mode clos, le niveau d'impact est réduit pour une meilleure exploration des fréquences très basses inférieures à 30 Hz, adapté pour une configuration Hi-Fi.



TECHNIQUE

Type

Caisson de basse actif bass-reflex

Phase variable

0° - 180°

Puissance

500 W RMS Classe D

Veille

Automatique

Haut-parleur

Grave : 300 mm membrane en fibre de verre

Entrées

Ligne L/R, LFE

Event

Orienté vers le sol

Réponse en fréquence (± 3 dB)

22 Hz - 200 Hz

Filtre subsonique

24 dB - 20 Hz

Fréquence de coupure variable

30 Hz - 200 Hz

DIMENSIONS - POIDS

Dimensions sans socle

H410 x L410 x P496

Poids net

29 kg

Dimensions avec socle

H467 x L440 x P520

PACKAGING

Dimensions packaging

L600 x H580 x P520 mm

Poids brut

33 kg

FINITIONS - CODES PRODUITS

Façade laquée, Caisson MDF, Placage vinyle

Finition
Noir

SKU
ELIPFSUB12BK

EAN
3700795193280



Finition
Blanc

SKU
ELIPFSUB12WT

EAN
3700795193297



Finition
Noir - Noyer

SKU
ELIPFSUB12WN

EAN
3700795193273

elipson® | Prestige Facet **SUB12**

2-WAY BASS-REFLEX SUBWOOFER

The Prestige Facet Sub range has been extended with the new PF Sub 12 active subwoofer.

This subwoofer is equipped with a 12" driver with a glass fibre cone for optimal frequency response thanks to its pistonic behaviour. It is designed as a bass-reflex "Down Firing" speaker in a rigid and inert enclosure, amplified by a 500 W class D module.

It also has a removable base that allows it to be used in closed mode by inserting a dense foam cylinder in the port. In bass-reflex mode, it offers a bass impact around the 40 Hz centre frequency for home theatre systems.

In closed mode, the impact level is reduced for better exploration of the very low frequencies below 30 Hz, suitable for a Hi-Fi setup.



TECHNICAL

Type Active subwoofer bass-reflex	Adjustable phase 0° - 180°
Power 500 W RMS Classe D	Standby mode Auto
Driver unit Woofers : 12" glass fibre cone	Inputs Stereo line level, LFE
Port Down-firing	
Frequency response (±3dB) 22 Hz - 200 Hz	
Subsonic Filter 24 dB - 20 Hz	
Variable cut-off frequency 30 Hz - 200 Hz	

DIMENSIONS - WEIGHT

Dimensions without base H410 x W410 x D496	Net weight 29 kg
Dimensions with base H467 x W440 x D520	

PACKAGING

Dimensions packaging W600 x H580 x D520 mm	Gross weight 33 kg
--	------------------------------

FINISHES - PRODUCTS CODES

Lacquered front panel, MDF box, Vinyl veneer

	Finish Black	SKU ELIPFSUB12BK	EAN 3700795193280
	Finish White	SKU ELIPFSUB12WT	EAN 3700795193297
	Finish Black - walnut	SKU ELIPFSUB12WN	EAN 3700795193273